REMARKS

The Drawing amendments find support in the specification. No new matter has been added. A request to approve drawing changes is included herewith. Applicants hereby respectfully request that the drawing amendments be entered.

The Specification has been amended to correct previously undetected informalities and provide citations. No new matter has been added.

The Abstract has been replaced. Please replace the Abstract with the new Abstract enclosed herewith on a separate paper. No new matter has been added.

Claims 1-15 have been canceled without prejudice. Claims 16-45 have been added to the present application. No new matter has been added.

The Summary of the Invention has been deleted.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached is captioned "Version with markings to show changes made." Additionally, attached is a replacement Abstract on a separate paper.

In conclusion, Applicants respectfully submit that claims 16-45 are in condition for allowance, and Applicants respectfully request allowance of such claims.

- 10 -

Atty. Docket No.: 31008.P017C Application No.: 10/081,446 Please charge any shortages and credit any overages to our Deposit

Account No. 501569.

Respectfully submitted, COLUMBIA IP LAW GROUP, PC

Date: <u>March</u> 13, 2002

Robert H. Chang Reg. No.: 48,765

Mailing Address:

10260 SW Greenburg Road Portland, Oregon 97223 Phone: (503) 595-2800 **VERSION WITH MARKINGS TO SHOW CHANGES MADE**

IN THE SPECIFICATION:

Please amend the specification as follows:

In the Summary of the Invention:

Please delete the Summary of the Invention.

SUMMARY OF THE INVENTION

A method and apparatus for processing and representing error messages

within a computer-aided design environment is described. An occurrence of a

software event that results in an error or a warning is recognized. An indication

of the error/warning is stored in an error/warning storage structure. A result is

returned from a function call that indicates that the error/warning indication has

been stored in the error/warning storage structure. Subsequent function call

returns do not indicate that the error/warning indication has been stored in the

error/warning storage structure. In one embodiment, a hierarchical graphical

error/warning-log-is provided that provides varying levels of error/warning

information in response to user input.

- 12 -

Atty. Docket No.: 31008.P017C Application No.: 10/081,446 In the Detailed Description:

Please replace the paragraph beginning at page 8, line 22, with the following

rewritten paragraph:

When an instruction cannot be executed properly, error notification is sent

to error/warning storage structure 380 by notifier 370. In one embodiment,

notifier 370 is a "thin wrapper" class that is described in greater detail below.

Alternatively, notifier 370 can be a sequence of instructions of function(C) 340 or

an independent called function (not shown in Figure 3), which results in higher

overhead than the thin wrapper class embodiment. Function(C) 340 returns

results to function(B) 320 via 350. Function(B) 320 in turn returns results to

function(A) 300 via 360.

Please replace the paragraph beginning at page 9, line 6, with the following

rewritten paragraph:

Based on results returned from function(B) 320, function(A) 300 is notified

that at least one error and/or warning occurred and that at least one called

function did not successfully complete execution. Function(A) 300 retrieves error

results from error/warning storage structure 380, via 390, to report the

error/warning results to the user of the computer aided design tool. One

embodiment for presenting the report is described in greater detail below.

- 13 -

Atty. Docket No.: 31008.P017C

Application No.: 10/081,446

In the Abstract:

Please replace the Abstract with the new Abstract enclosed herewith on a separate paper.

The invention includes computer instructions that operate to generate a failure indication upon encountering a failure during an operation performed for a user design. The instructions further operate to automatically facilitate a user in determining a solution for the failure. As a result, the invention provides improved error reporting and recovery.

A method and apparatus for processing and representing error messages within a computer-aided design environment is described. The present invention allows error/warning information to be stored in a central storage location by the function in which the error/warning causing fault occurs. The function then returns a result indicating that the function did not perform as expected. The calling function does not add an error/warning message of its own when returning, if necessary, to another calling function. Thus, only a single warning/error message can be stored and used for reporting the fault that caused the error/warning. In one embodiment, a hierarchical graphical error/warning log provides varying levels of error/warning information in response to user input.

- 14 -

Atty. Docket No.: 31008.P017C Application No.: 10/081,446